



HALVERSON WOOD PRODUCTS SPECS

| | GRAPPLE HWP-125GS | PROCESSOR HWP-120 | PROCESSOR HWP-140B | Inverted Splitter |
|-----------------------------|--|--|--|--|
| LENGTH | 33" | Travel= 99" Working= 121" | Travel= 102" Working= 126" | |
| WIDTH | 56" | 55" | 55" | |
| HEIGHT | 41" | 51" | 51" | |
| WEIGHT | 645 lbs | 975 lbs | 1450 lbs | |
| MATERIAL | 3/8"-5/8" Steel | 1/4" High Tensile Steel | 3/8" Steel | |
| HYDRAULICS | | | | |
| -MINIMUM PRESSURE | 2850 | 2850 | 2850 | |
| -FLOW | 12-18 gpm | 12-18 gpm | 15.5-23 gpm | |
| -CONNECTIONS | 1-Pressure, 1-Return 1-Case Drain | 1-Pressure, 1-Return 1-Case Drain | 1-Pressure, 1-Return 1-Case Drain | 1-Pressure, 1-Return |
| MAX LOG DIAMETER | 24" | 15" | 15" | |
| MIN LOG DIAMETER | 3" | NA | NA | NA |
| MAX LOG LENGTH | NA | 12' | 12' | 29" |
| MIN LOG LENGTH | NA | 6' | 6' | NA |
| FIREWOOD CUT LENGTHS | NA | Up to 22" | Up to 22" | Up to 29" |
| SAW BAR | 29-1/2", 74.93 cm | 25"(642cm)Harvester | 25"(642cm)Harvester | NA |
| SAW CHAIN | .404 pitch/18HX series | .404 pitch/18HX series | .404 pitch/18HX series | NA |
| SAW MOTOR | Bent Axis Piston | Bent Axis Piston | Bent Axis | NA |
| SAW OILER | Automatic 2 Qt Tank | Automatic 2 Qt Tank | Automatic 2 Qt Tank | NA |
| MAX SAW CUT | 27" | 15" | 18" | NA |
| SPLITTER CYLINDER | NA | Standard 3.5" x 24" stroke | Custom 3.5" x 24" stroke | Custom 4" x 24" Stroke |
| SPLITTER FORCE | NA | 27,406 | 27,406 | 35,794 |
| SPLITTING WEDGE | NA | 4 way fixed | 4 way manually adjustable | 4 way manually adjustable |
| IN-FEED | Grapple | Sliding trough carries log to wedge | Sliding trough carries log to wedge | NA |
| MOUNTING | Universal Quick Attach SAE Spec J2513 | Universal Quick Attach SAE Spec J2513 | Universal Quick Attach SAE Spec J2513 | Universal Quick Attach SAE Spec J2514 |
| MEASURING | None | None | Manual moveable device | None |